



# DTV (UHF) Full Service Mask Transmit Bandpass Filter

MFC supplies critical equipment for your UHF Repack requirement.

This filter, along with a UHF transmitter, allows your system to conform to the FCC spectral mask.



## Model 19946-(Ch) 1 kW (Fixed)

Specifications	
Channel Option	Ch 14-36
Insertion Loss @ Fo	0.8 dB Approx
Passband	(Fo) ± 2.7 MHz
Passband Loss	1.2 dB Approx @ Passband Edges
Passband VSWR	1.2:1 Max
Passband Power	1 kW Max - continuous
Passband Delay Variation	200 nSEC Max
Rejection	6 dB Approx @ (Fo) ± 3.5 MHz 55 dB Min @ (Fo) ± 6.0 MHz 85 dB Min @ (Fo) ± 9.0 MHz
Impedance	50 Ohms
Connectors	See chart
Operating Temperature	25°C, ± 10°C

### Features :

- 8-pole design provides ultra-selectivity for UHF broadcasts
- Optional connectors available
- Special configurations available upon request (e.g. multi-channel combining)
- 50 ohm Impedance

(*)	Connector Option
NF	Type N Female
78	7/8 EIA Flange
DN	7/16 DIN Female



**MICROWAVE FILTER COMPANY, INC.**

6743 Kinne Street, East Syracuse, NY 13057 • Toll Free: 800-448-1666 or 888-206-6610

www.microwavefilter.com • email: mfcsales@microwavefilter.com • International: 315-438-4700